dropt-cli

Chiayu Sun and Haopin Wu

Jul 24, 2020

CONTENTS

1	Quickstart	3
2	Prepare A Project	7
3	Project Control	11
4	Project Inspection	13
5	Advisor & Search Space	21
6	Authors	25
7	License	27
8	CHANGELOG	29
9	Links	31

Dr.Opt is an ML model optimization platform consisting of

- Hyper-parameter optimization service
- Client Python package for service connoction & project control
- Project visualization & analysis via WubUI

Please read Quickstart to begin.

ONE

QUICKSTART

Here we illustrate how one can create and run a Dr.Opt project based on our trial examples.

1.1 Prerequisites

Before starting, make sure the following things are installed in your system:

- Python 3.6 or newer
- pip

1.2 Registration/Get Access Token

1. Go to Dr.Opt server webpage and click Sign in.

Q	Dr.Opt is an optimization platform and API designed to give you optimized values for
Sign in	hyperparameters, which maximizes your moder's predictive accuracy.
About Us	
Delivery Information	
Privacy Policy	
Terms & Conditions	

2. Click Continue and finish the registration. User will be notified via email once the registration is approved.

A DECK		
	New User	Returning User
	Register Account	Login
\bigcirc	Create an account to start automated optimization and get project analysis.	E-Mail Address
29		E-Mail Address
		Password
Sign in	Continue	Forgotten Password
		Login
About Us		
Delivery Information		
Privacy Policy		
Terms & Conditions		

3. In My Account page click My tokens

	Recourt	
- Theoreman -	My Account	
Haopin Wu		
1001 Daxue Road	Edit your account information	
Projects		
Account		
🕞 Logout		
About Us		
Delivery Information		
Privacy Policy		
Terms & Conditions		
	-	

4. Copy the api token for later use.

1.3 Run our examples

1. Download our examples from GitHub:

```
$ git clone https://github.com/GoEdge-ai/dropt-example.git
```

2. Move to the directory of a trial example:

\$ cd dropt-example/trials/func-eggholder

3. Install required Python package:

```
$ pip install -r requirements.txt
```

4. Create and run a new Dr.Opt project with our control script, in which TEKON is the access token of your account:

\$ droptctl -t TOKEN create

5. Inspect the result on the Dr.Opt server webpage.

1.4 Your Turn!

We just showed you how to run a our example project. To run your own project, please refer to the following sections:

- Prepare A Project
- Project Control
- Project Inspection

PREPARE A PROJECT

In Dr.Opt, a parameter optimization task is called a **project**. Before starting a new project, user needs to prepare a project folder containing all necessary files. Here we will brief how it is done.

2.1 Folder Structure

The following diagram depicts the minimal structure of a project folder:

```
MyProject

config.json

mymodel.py
```

- mymodel.py: A Python file for the model to be tuned
- config.json: A JSON file describing the configuration of the project

Note that the names of both files are customizable.

2.2 mymodel.py

The Python file should contain the following function:

```
def run(params):
    ...
    return metric
```

- The input params represents the hyper-parameter configuration for the model.
- The output metric measures the performance, such as accuracy or latency, of the model.

Here is an example how run should work:

```
>>> from mymodel import run
>>> params = {
    ... "max_depth": 10,
    ... "gamma": 0.25,
    ... "alpha": 0.5,
    ... "learning_rate": 0.001,
    ... "subsample": 0.75,
    ... "colsample": 0.75
}
```

(continues on next page)

(continued from previous page)

```
>>> run(params)
0.732
```

2.3 config.json

We consider an example config file:

```
{
    "config": {
        "experimentName": "titanic-xgboost",
        "maxExecDuration": "1h",
        "maxTrialNum": 10,
        "parentProject": "None",
        "model": "model",
        "updatePeriod": 60,
        "tuner": {
            "builtinTunerName": "TPE",
            "classArgs": { "optimize_mode": "maximize" }
        }
   },
    "params": {
        "booster": "gbtree",
        "verbosity": 0,
        "base_score": 0.5,
        "colsample_bylevel": 1,
        "n_estimators": 50,
        "objective": "binary:logistic",
        "max_depth": 5,
        "gamma": 0.2,
        "subsample": 0.8,
        "colsample-bytree": 0.8,
        "lambda": 1,
        "alpha": 0.25,
        "eta": 0.01,
        "min_child_weight": 1.0
    },
    "search_space": {
        "max_depth": {"_type": "randint", "_value": [1, 5]},
        "gamma": {"_type": "uniform", "_value": [0.1, 1.0]},
        "subsample": {"_type": "uniform", "_value": [0.1, 1.0]},
        "colsample_bytree": {"_type": "uniform", "_value": [0.1, 1.0]},
        "alpha": {"_type": "uniform", "_value": [0.1, 1.0]},
        "eta": {"_type": "uniform", "_value": [0.1, 1.0]}
    }
}
```

Three main sections should be included in the JSON file:

2.3.1 config

This section contains config options of the project, which includes:

experimentName (string)

• Name of the project, which will be shown on the Dr.Opt webpage

maxTrialNum (number/integer)

• The maximum number of trials of this project

maxExecDuration (number/integer)

- The expected maximal execution time of the project in *hour* (default: 12 hrs)
- If the experiment time exceeds the **maxExecDuration**, the project state will change to "finish" and inpcomplete suggestions will be discarded.

parentProject (string)

- The parent project of the current one
- (Coming in the future) The newly created project can inherent the properties of the parentProject
- Just set to None for now

model (string)

• The Python file of the model to be tuned (without file extension)

mode (string)

• The optimization mode of the project. It can be max (default) or min.

updatePeriod (number/integer)

• The update period of the webpage (in *second*)

tuner (object)

- parameter search algorithm
- See page Advisor for detail

2.3.2 params

This section consists of default hyper-parameter of the model. Its format should conincide with that of input of run (see section *mymodel.py*).

2.3.3 search_space

This section describes the search space. Please read page Search Space for detail.

THREE

PROJECT CONTROL

Once a project folder is prepared, user can manage the project via the project control droptctl, which is included in the Dr.Opt client package dropt-cli. To install it, simply run

```
$ pip install dropt-cli
```

3.1 Basic Syntax

Here is the basic syntax of droptctl:

\$ droptctl -s ADDRESS -p PORT -t TOKEN CMD

- ADDRESS and PORT indicate which Dr.Opt server droptctl will connect to. If not given, default Dr.Opt server will be used.
- TOKEN is the unique identification of each user. It can be found on one's own My account page.
- CMD is the command to be sent. Currently, two commands are supported:
 - create
 - resume

3.2 Create

```
$ droptctl -t TOKEN create -c CONFIG_FILE
```

Create and run a new project based on config file CONFIG_FILE. The default config file is config.json.

3.3 Resume

User may resume a project if interrupted.

```
$ droptctl -t TOKEN resume
```

A prompt will show all ongoing projects and user selects one to resume.

PROJECT INSPECTION

Dr.Opt provides multiple visualization tools for analyzing projects. This page aims to introduce how to inspect Dr.Opt projects.

4.1 Project List

After login to the user account, the project list will first show up. It lists each project by the project name, the number of suggestions, and the best result.

Project List



The project page can be opened by clicking the project block.

4.2 Summary

Summary

	mnist-pytorcl	h Buttering Butt	Drag the middle and edges of the selection box to change the range above					
Show 10 entries	index *	tatch size	gamma	hidden size	r B	value		
		32	0.006	128	0.0001	0.6019		
	2	128	0.052	128	0.0001	2.2763		
	3	16	0.977	1024	0.0001	0.3833		
	4	32	0.932	512	0.1	0.0232		

The summary page composes of three main parts:

- project card (project name & the best result)
- optimizing progress chart
- suggestion table

4.2.1 Project Card

Similar to the blocks of the project list, the project card indicates the name of the project and the best optimization result. The best value depends on the mode (minimize or maximize) set in the project config.

4.2.2 Optimizing Progress Chart

Summary



The chart in the upper-right corner plots the objective value of each trial. Users can evaluate the optimization progress by the line chart (e.g., Does it keep improving? Do the objective values fall in a certain range?)

4.2.3 Suggestions Table

The table below collects the suggestion values of a project. Each row represents the suggestion of a trial.

alpha 🔍	colsample_bytree	eta 🕴	gamma 🖗	max_depth	subsample	value 🕶
0.494	0.947	0.197	0.373	3	0.834	0.8373
0.201	0.434	0.7	0.383	2	0.889	0.8351
0.114	0.856	0.289	0.722	4	0.78	0.835
0.403	0.647	0.96	0.275	2	0.688	0.8305
0.202	0.695	0.512	0.263	4	0.325	0.8294
0.968	0.661	0.855	0.862	3	0.971	0.8283

The table can be sorted by clicking the column name. Take the following picture as an example, the user can find out the suggestions that obtain the best results by sorting by the object value.

4.3 Analysis

The analysis page contains multiple charts to visualize the suggestion results. It comprises four tabs:

4.3.1 Dot Plots



Dot plots demonstrate the distribution & performance of each hyper-parameter. The plotted data of both the x-axis and the y-axis can be switched by the drop-down list.

4.3.2 Histograms



Histograms illustrate the distribution of the suggested hyper-parameter values. That is, the range that the tuning algorithm suggests the most. Besides the number of suggestions, the performance is presented by the color-mapping.

4.3.3 Parameter Analysis

The parameter analysis page illustrates a parallel coordinates plot. It is commonly used for visualizing & comparing many variables together.



As for parameter optimization, it is practical for analyzing the well-performed range and the relationship between each parameter.

4.3.4 3D Plot & Feature Importance

The tab "3d plot" contains a 3-dimension surface plotter and a feature importance chart.

Analysis



The 3D plotter can visualize the data by a surface or a scatter plot.



As for the tasks that have a constraint search space (e.g., some hyper-parameter combinations may directly fail), this kind of visualization may be useful to find out the valid range of value.

4.4 Properties

The detailed configuration of a project can be found on the properties page, which can be accessed by the sidebar.

arriant ID *	name 2	inter 10	anarysis (work 1	parent project 1	model 1	addoor 1	mate 1	create date 1
140	titarie sghoost	12	50	50	Norse	- Alle	Exiliation	max	2820-67-20 16:25:39
Showing 1 to 1 of 1 entries									Previous 1 Next
Property list									
	turne	*	type (min / µ 0		max (a 1)		options / unit it
	101		uniture .		8.1		1.8		
	cotsample_hytre		uniform		0.1		1.0		
	81	4	untern		0.1		1.0		
	gamma		uniform		0.1		1.0		
	mux_dept		randine		4		5		
	sidnangi		unform		-0.1		1.0		
Showing 1 to 6 of 8 entries									Previous 1 Next
Danger Zone	6								

Through the properties page, the user can confirm the project settings, view the parameter search space, and delete the project.

4.5 Suggestions

The suggestions page lists the full suggestion history. It is similar to the table of the summary page, but the main difference that the suggestions page does not conclude the progress plot. We plan to add more features for this page and please look forward to our update!

FIVE

ADVISOR & SEARCH SPACE

5.1 Advisor

Dr.Opt supports the following advisors:

Advisor	Description				
Anneal	Begin with sampling from the prior and tends over time to sample from points closer and				
	closer to the best ones observed.				
Evolution	Randomly initialize a population based on the search space. It chooses better ones and				
	does some mutation on them to get the next generation. Evolution may require many trials				
	to work (ref).				
Gaussian Process	A sequential model-based optimization (SMBO) approach that uses Gaussian Process as				
(coming soon)	the surrogate (ref).				
Grid Search	Perform an exhaustive search in a specified subset of the parameter space.				
Random	Randomly select hyper-parameter combinations in the search space. Researches show that				
	it might be surprisingly effective (ref).				
TPE	A sequential model-based optimization (SMBO) approach that uses Tree-structured				
	Parzen Estimators as the surrogate (ref).				

5.1.1 Anneal

Arguments

optimize_mode maximize (default) or minimize

```
{
    "builtinTunerName": "Anneal",
    "classArgs": {"optimize_mode": "maximize"}
}
```

5.1.2 Evolution

Arguments

optimize_mode maximize (default) or minimize

population_size The initial size of the population

Example

```
{
    "builtinTunerName": "Evolution",
    "classArgs": {
        "optimize_mode": "maximize",
        "population_size": 100
    }
}
```

5.1.3 Grid Search

Arguments

None

Config example

{

}

"builtinTunerName": "GridSearch"

5.1.4 Random

Arguments

None

Config example

{

"builtinTunerName": "Random"

5.1.5 TPE

Arguments

optimize_mode maximize (default) or minimize

```
{
    "tuner": {
        "builtinTunerName": "TPE",
        "classArgs": {"optimize_mode": "maximize"}
    }
}
```

5.2 Search Space

Each parameter to search is assigned with certain space type. Dr.Opt currently supports the following search space types:

5.2.1 choice

Choose from a list of available options.

Format A list of of numbers or strings, e.g., [0.1, 0.01, 0.001, 0.0001] or ["Adam", "SGD", "Adadelta"]

Example

```
{
    "learning_rate": {
        "_type": "choice",
        "_value": [0.1, 0.01, 0.001, 0.0001]
    }
}
```

5.2.2 randint

Choose a random integer within an interval.

Format [lower_bound (inclusive), upper_bound (exclusive)]

Example

```
{
    "batch_size": {
        "_type": "randint",
        "_value": [8, 65]
    }
}
```

5.2.3 uniform

Choose a number randomly from a uniform distribution on an interval.

Format [lower_bound (inclusive), upper_bound (exclusive)]

```
{
    "droptout_rate": {
        "_type": "uniform",
        "_value": [0.1, 0.5]
    }
}
```

5.2.4 quniform

Choose a number randomly from an interval descretized by a fixed step size.

Format [lower_bound (inclusive), upper_bound (exclusive), step]

Example

```
{
    "input_size": {
        "_type": "quniform",
        "_value": [224, 417, 32]
    }
}
```

Note: In this example, the possible values are: 224, 256, 288, 320, ..., 384, 416.

5.2.5 normal

Choose a number randomly from a normal discribution with prescribed mean (μ) and standard deviation (σ).

Format $[\mu, \sigma]$

```
{
    "dropout_rate": {
        "_type": "normal",
        "_value": [0.5, 0.1]
    }
}
```

SIX

AUTHORS

6.1 Core Development Team

- Chiayu Sun <chiayusun.cs08g@nctu.edu.tw>
- Haopin Wu <psistwu@outlook.com>

SEVEN

LICENSE

MIT License

Copyright (c) 2020 Haopin Wu Copyright (c) 2019-2020 Chiayu Sun Copyright (c) 2014-2015 SigOpt Inc.

Permission **is** hereby granted, free of charge, to any person obtaining a copy of this software **and** associated documentation files (the "Software"), to deal **in** the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, **and/or** sell copies of the Software, **and** to permit persons to whom the Software **is** furnished to do so, subject to the following conditions:

The above copyright notice **and** this permission notice shall be included **in** all copies **or** substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

EIGHT

CHANGELOG

dropt-cli uses Semantic Versioning.

8.1 0.9.0

- Comprehensive documentation
- Migrate examples to an indivisual repo
- Simplify the readme file

NINE

LINKS

Dr.Opt service cloud https://dropt.goedge.ai dropt-cli repo https://github.com/GoEdge-ai/dropt-cli dropt-example repo https://github.com/GoEdge-ai/dropt-example